

PRODUCT DATA SHEET

WDG-Insitu Flue Gas Oxygen Analyzer

Field-serviceable direct-sensing insitu probe

The WDG-Insitu flue gas oxygen (O₂) probe differs from all other O₂ insitu probes. The unique inner/outer probe design facilitates removal of cell, heater and thermocouple assembly through the probe head.

A combination of component access and reduced utility requirements provides a cost-effective, reduced-maintenance solution for today and tomorrow's gas, oil and coal-fired boiler operations.

Completely field-serviceable

Once the inner probe assembly is removed, the outer probe support pipe allows straight run access to the insitu filter for cleaning with compressed air.

Reduced utility requirements

The inner probe assembly also exposes the reference side of the zirconium cell to ambient air, eliminating the need for instrument air utilities at the probe mounting location.

Series 2000 Control Unit

Maximize integration with your existing plant or process control system with the Series 2000 Control Unit:

- Four-line local display
- Analog outputs
- Alarms
- Expanded system diagnostics
- Autocalibration option



KEY BENEFITS

- Hot/wet O₂ analysis
- Different probes length
- Easy to maintain
- Detachable probe
- Completely field serviceable

APPLICATIONS

- Combustion control
- Suitable for applications where the flue gas temperature does not exceed 800°C (1472°F)

KEY MARKETS

- Power generation
- Thermo-electric plants
- Pre-heaters

PERFORMANCE SPECIFICATIONS

Sensor Specifications

Principle of operation	Zirconium oxide (ZrO ₂) for net O ₂ measurement
Output range	O ₂ : From 0-1% to 0-100%
Accuracy	±1% of measured value or ±0.05% O ₂ , whichever is greater
Response	63% of a step change < 20 seconds.
Drift	< 0.1% of cell output per month (< 0.005% O ₂ per month with 2% O ₂ applied)
Linearity	±1% of output span
Repeatability	±1% of output span
Max. flue gas temperature	800°C (1472°F). Probe material highly corrosion-resistant
Sample pressure	±10 in. water gauge
Environment	Ambient temperature: -20 to 71°C (-5 to 160°F) Relative humidity: 10 to 90%, noncondensing
Enclosure	UL type (NEMA 4X) standard. Optional explosion-proof and purged versions available. (Purged version for sub atmospheric process pressure only)
Power requirements	115 VAC, ±10%, 47-63 Hz; 230 VAC, ±10%, 47- 63 Hz; 150 VA max.

Series 2000 Control Unit Specifications

Display	Four-line x 20-character vacuum fluorescent. Displays combinations of O ₂ , time and date, cell temperature, user-programmable text, thermocouple mV or cell mV. Password protection, programmable pressure compensation and context sensitive help are also provided
Analog output	Two isolated linear current outputs. Select O ₂ , cell temperature, thermocouple mV or cell mV. Each output can be 4-20 mA, 0-20 mA, 20-4 mA or 20-0 mA and is fully scalable. Hold or track during calibration and select degree of damping. Maximum load 1200 ohms
Alarms	Two independent O ₂ alarms, each high- or low-selectable. One alarm can be assigned as O ₂ , calibrate or verify Set relays to energize or de-energize on alarm
Contact rating	0.5A, 30V, 10VA max. non-inductive load, AC or DC
Diagnostics	Watchdog timer and service alarms. System test for A/D, RAM, EEPROM and keypad. Display line four reserved for full-text error and diagnostic messages. 20-entry event log
Communications	RS-485 two-way addressable
Environment	Ambient temperature: -10 to 50°C (14 to 122°F) Relative humidity: 10 to 80%, non-condensing
Enclosure	Standard weatherproof NEMA 4 (IP 56) wall/panel mount. Optional GP (general purpose) wall mount, GP 19" rack mount, GP panel mount, or stainless steel weatherproof NEMA 4X (IP 56) wall/panel mount. All are UL listed for NEC Class I, Division 2 areas. Purged and explosion-proof versions also available
Power requirements	Nominal 115-230 VAC ±10%, 47-63 Hz; 75 VA max
System compliance	EMC Directive 2004/108/EC Low Voltage Directive 73/23/EEC

SALES, SERVICE & MANUFACTURING

USA - Pennsylvania

150 Freeport Road
Pittsburgh PA 15238
Tel: +1 412 828 9040
Fax: +1 412 826 0399

USA - Delaware

455 Corporate Blvd.
Newark DE 19702
Tel: +1 302 456 4400
Fax: +1 302 456 4444

Canada - Alberta

2876 Sunridge Way NE
Calgary AB T1Y 7H9
Tel: +1 403 235 8400
Fax: +1 403 248 3550

WORLDWIDE SALES AND SERVICE LOCATIONS

USA

Tel: +1 713 466 4900
Fax: +1 713 849 1924

Brazil

Tel: +55 19 2107 4100

France

Tel: +33 1 30 68 89 20
Fax: +33 1 30 68 89 99

Germany

Tel: +49 2159 9136 0
Fax: +49 2159 9136 39

India

Tel: +91 80 6782 3200
Fax: +91 80 6780 3232

Singapore

Tel: +65 6484 2388
Fax: +65 6481 6588

China

Beijing
Tel: +86 10 8526 2111
Fax: +86 10 8526 2141
Chengdu
Tel: +86 28 8675 8111
Fax: +86 28-8675 8141
Shanghai
Tel: +86 21 5868 5111
Fax: +86 21 5866 0969



© 2018, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0162 Rev 7 (0818)
One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.

